




marlow industries, inc.®
Subsidiary of II-VI INCORPORATED

TECHNICAL DATA SHEET




XLT2386

Single-Stage Thermoelectric Cooler

PERFORMANCE VALUES

Hot Side Temperature (°C)	27°C	50°C
Δ Tmax (°C-dry N ₂):	56.5	64.0
Qmax (watts):	72	79
Imax (amps):	13.9	13.8
Vmax (vdc):	8.0	8.8
AC Resistance (ohms):	0.47	---

MECHANICAL CHARACTERISTICS




ORDERING OPTIONS

Model Number	Description
XLT2386-03AC	No metallized exterior, with Leadwires
XLT2386-04AC	No metallized exterior, without Leadwires
XLT2386-05AC	No metallized exterior, Leadwires, Diced
XLT2386-07AC	No metallized exterior, Leadwires, Sealed
XLT2386-11AC	No markings on hot or cold side

AVAILABLE MODIFICATIONS

Specifically designed for thermal cycling applications. Capable of rapid heating and cooling rates. Proven High Reliability (Data available upon request). Rugged construction. Porched configuration for enhanced leadwire strength. Leadwires attached with 183°C solder. Rated operating temperature of 130°C. Height tolerance of ± 0.0005 in. (± .001 mm) allows for multiple module applications.
-04AC, -11AC: RoHS 2002/95/EC Compliant.

ENVIRONMENT: ONE ATMOSPHERE DRY NITROGEN



For performance information in a vacuum or with hot side temperatures other than 27°C or 50°C, consult one of our Applications Engineers.

Installation

XLT coolers are typically mounted under compression using thermal grease or flexible graphite products. Consult Marlow Industries' Thermoelectric Installation Guide for more details. For additional information, please contact one of our application engineers for technical support.

CONTACT US:

For customer support or general questions please contact a local office below or consult our website for distributor information.

Marlow Industries, Inc.
 10451 Vista Park Road
 Dallas Texas 75238-1645
 214-340-4900 (tel)
 214-341-5212 (fax)
 www.marlow.com

Marlow Industries Europe GmbH
 Im Tiefen See 58
 64293 Darmstadt - Germany
 Tel.: +49 (0) 6151 8806 -0
 Fax.: +49 (0) 6151 8806 9455

II-VI Japan Inc.
 WBG Marive East 17F
 2-6 Nakase, Mihama-ku
 Chiba-Shi, Chiba 261-7117
 Japan
 81 43 297 2693 (tel)
 81 43 297 3003 (fax)
 center@ii-vi.co.jp
 www.ii-vi.co.jp

II-VI Singapore Pte., Ltd.
 Blk. 5012, Techplace II
 #04-07 & 05-07/12, Ang Mo Kio Ave. 5
 Singapore 569876
 (65) 6481 8215 (tel)
 (65) 6481 8702 (fax)
 info@ii-vi.com.sg
 www.ii-vi.com.sg

Marlow Industries China, II-VI
 Technologies Beijing
 A subsidiary of II-VI Incorporated
 Rm 202, 1# Lize 2nd Middle Road
 Wangjing, Chaoyang District
 Beijing 100102 China
 010-64398226 ext 105 (tel)
 010-64399315 (fax)
 info@iivibj.com